Atty. Docket No. NOKIA, 4006US

#### IN THE CLAIMS:

Please amend the claims in accordance with the following listing of claims:

1-29 Cancelled.

## BEST AVAILABLE COPY

- 30 (Currently Amended) A telephone system for a vehicle comprising:
- a vehicle transceiver, on board said vehicle, and connectable to a cellular telephone network for bi-directional communication therewith;
- a server terminal, on board said vehicle, connected to said transceiver and having an identification address;
- a plurality of user terminals, distributed on board the vehicle, each capable of accepting an identity of a user of the cellular telephone system and each connected to said server terminal whereby a plurality of users may communicate simultaneously with said network via the server terminal; and
- a location data base for identifying users of the cellular telephone system when their identifies are accepted by respective user terminals and for associating those users with said identification address to permit communication to be established between those users and the cellular telephone system via the server terminal;

a plurality of interface systems each for providing a communication path between said transceiver and a switching network within a respective region, the switching network being connected to said telephone network and connectable to at least one of said interface systems when the vehicle is located in the region corresponding to that interface system thereby providing a communication path between said transceiver and said telephone network; and

control apparatus operable to select which one of said interface systems should provide the communication path to the transceiver when the vehicle is located in the regions corresponding to a plurality of interface systems, the control apparatus being further operable to control simultaneously the handover of said established communication when the vehicle moves from a first one of the said regions to a second one of said regions, wherein said identification address remains unaltered as said vehicle moves from said first to said second respective regions.

### BLUI AVAILAULE COPY

Atty. Docket No. NOKIA.4006US

- 31. (Cancelled)
- 32. (Previously Presented) A telephone system according to claim 30 in which said location data base is connected to said telephone network and is accessible to enable said network to locate each of said accepted users and thereby enable bi-directional communication between said telephone network and each of said identified users.
- 33. (Cancelled)
- 34. (Cancelled)
- 35. (Previously Presented) A telephone system according to claim 30 wherein said telephone system allows bi-directional communication between each user terminal in said vehicle and said telephone network.
- 36. (Previously Presented) A telephone system according to claim 31 wherein each said interface system comprises a server satellite and at least one associated ground earth station.
- 37. (Previously Presented) A telephone system according to claim 30 wherein said vehicle transceiver comprises a aeronautical earth station for bi-directional communication via satellite to a ground earth station which is connectable to the telephone network.
- 38. (Previously Presented) A telephone system according to claim 30 wherein said location database is stored in a mobile switching centre.
- 39. (Previously Presented) A telephone system according to claim 30 wherein said user terminal is connected to said server terminal via a first fixed connection and said server terminal is connected to said vehicle transceiver via a second fixed connection.

### **BEST AVAILABLE COPY**

Atty. Docket No. NOKIA.4006US

- 40. (Currently Amended) A telephone system according to claim 390 wherein said first fixed connection is RS-232 serial bus of USB.
- 41. (Currently Amended) A telephone system according to claim 390 wherein said first fixed connection is a universal serial bus (USB).
- 42. (Currently Amended) A telephone system according to claim 399 wherein said second fixed connection is a CEPT-E1 connection.
- 43. (Previously Presented) A telephone system according to claim 30 wherein said user terminal comprises a cellular phone unit provided with an identification receptor for a subscription identifier of a user of the cellular telephone system.
- 44. (Previously Presented) A telephone system according to claim 43 in which the identifier is a S1M card or Smart Card.
- 45. (Previously Presented) A telephone system according to claim 30 wherein said user terminal comprises a phone receptor for receiving a user cellular phone.
- 46. (Previously Presented) A telephone system according to claim 45 wherein said user cellular phone is adapted to deactivate radio transmission by the cellular phone when said cellular phone is connected to said phone receptor.
- 47. (Previously Presented) A telephone system according to claim 30 wherein said server terminal comprises a personal computer (PC).
- 48. (Previously Presented) A telephone system according to claim 30 wherein said location database identifies which user of the cellular telephone system is connected to a user terminal by a subscription identifier.

# BEST AVAILABLE COPY

Atty. Docket No. NOKIA.4006US

- 49. (Previously Presented) A telephone system according to claim 31 wherein said switching network and control apparatus comprise an internet network.
- 50. (Previously Presented) A telephone system according to claim 49 wherein said location database is an Intranet location register.
- 51. (Previously Presented) A telephone system according to claim 30 wherein the vehicles is an aircraft.
- 52. (Currently Amended) A method of operating a telephone system within a vehicle to enable a plurality of users to simultaneously communication with a ground base cellular telephone system, which method comprises:

establishing a fixed connection through a plurality of user terminals distributed on board the vehicle to a server terminal having an identification address;

establishing a connection between said server terminal and an onboard transceiver;

identifying users of the cellular telephone system when their identifies are accepted by respective user terminals; and

associating identified users with said identification address to permit simultaneous communication to be established between those users and the cellular telephone system via the server terminal.

establishing a communication path between said transceiver and a switching network via a satellite and associated ground station when said vehicle is in a respective region wherein said switching network is connected to said cellular telephone system;

selecting which satellite should provide a communication path to the transceiver when the vehicle is located in a region corresponding to a plurality of satellites; and

controlling simultaneously the handover of said established connection when the vehicle moves from a first one of said respective regions to a second one of said respective, wherein said identification address remains unaltered as said vehicle moves from said first to said second respective regions.

# BEST AVAILABLE COPY

Atty. Docket No. NOKIA.4006US

- 53. (Cancelled)
- 54. (Cancelled)
- 55. (Previously Presented) aircraft.
- 56. Cancelled.

A method according to claim 52, wherein the vehicle is an